

[illegible]

DOOR SCHEDULE											(SEE DOOR NOTES THIS SHEET)
NO.	TYPE	SIZE			MATERIAL			FINISH		REMARKS	①
		WIDTH	HT.	THICK	CORE	DOOR	FRAME	DOOR	FRAME		
①	A	3'-0"	7'-0"	1 1⁄4"	ALUM./GL	ALUM./GL	ALUM	SATIN-ANOD	SATIN-ANOD	PROVIDE TEMPERED GLASS DOOR PANEL	
②	B	3'-0"	7'-0"	1 1⁄4"	WD	WD/GL	HM *	SEAL/CLR	PAINT	SELECT D.F. SINGLE LITE FRENCH DOOR w/ TEMP. GLASS	UNDERCUT
③	B	3'-0"	7'-0"	1 1⁄4"	WD	WD/GL	HM *	SEAL/CLR	PAINT	SELECT D.F. SINGLE LITE FRENCH DOOR w/ TEMP. GLASS	UNDERCUT
④	B	3'-0"	7'-0"	1 1⁄4"	WD	WD/GL	HM *	SEAL/CLR	PAINT	SELECT D.F. SINGLE LITE FRENCH DOOR w/ TEMP. GLASS	UNDERCUT
⑤	B	3'-0"	7'-0"	1 1⁄4"	WD	WD/GL	HM *	SEAL/CLR	PAINT	SELECT D.F. SINGLE LITE FRENCH DOOR w/ TEMP. GLASS	UNDERCUT
⑥	B	3'-0"	7'-0"	1 1⁄4"	WD	WD/GL	HM *	SEAL/CLR	PAINT	SELECT D.F. SINGLE LITE FRENCH DOOR w/ TEMP. GLASS	UNDERCUT
<div>⚠️ * PROVIDE H.M. FRAMES WITH WELDED CORNERS</div>											

WINDOW SCHEDULE							(SEE WINDOW NOTES THIS SHEET)
TYPE	SIZE (WIDTH X HEIGHT)	MATERIAL		FINISH		REMARKS	
		FRAME	GLAZING	FRAME	GLAZING		
① A	6'-4" x 8'-0" VERIFY	ALUM	DBL	CLR. ANOD.	CLEAR	PROVIDE TEMPERED GLASS PER "WINDOW NOTES" #2	
② B	4'-0" x 2'-4" VERIFY	WOOD	SSL	WOOD	CLEAR	MATCH EXISTING HIGH WINDOWS SASH & FRAMES	

DOOR NOTES

1. EXIT DOORS SHALL SWING IN THE DIRECTION OF EXIT TRAVEL WHEN SERVING ANY HAZARDOUS AREA OR WHEN SERVING AN OCCUPANT LOAD OF 50 OR MORE (TITLE 24, 1003.3.1.5)
2. EXIT DOORS SHALL BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT. FLUSH BOLTS OR SURFACE BOLTS ARE PROHIBITED. THE UNLATCHING OF ANY LEAF SHALL NOT REQUIRE MORE THAN ONE OPERATION. (TITLE 24, 1003.3.1.8)
3. WIDTH & HEIGHT OF EXIT DOORWAYS TO COMPLY WITH TITLE 24, (TITLE 24, 1003.3.1.3)
4. THE BOTTOM 10" OF ALL DOORS SHALL HAVE A SMOOTH UNINTERRUPTED SURFACE.
5. ALL MEANS OF EGRESS DOORS SHALL COMPLY WITH THE REQUIREMENTS OF SECTION 1008.1 AND SECTION 1010.2.
 - a. MEANS OF EGRESS DOORS SHALL BE READILY DISTINGUISHABLE FROM THE ADJACENT CONSTRUCTION AND FINISHES WITH NO MIRRORS, CURTAINS, DRAPES, DECORATIONS, OR SIMILAR MATERIAL.
 - b. REQUIRED EXIT DOORS SHALL HAVE NOT LESS THAN 32-IN. CLEAR WIDTH, 80-IN. CLEAR HEIGHT, AND SHALL BE AT LEAST 60 DEGREES OF OPENING 90 DEGREES. THE MAXIMUM SWINGING DOOR LEAF WIDTH IS 4-FT. NOMINAL.
 - c. EGRESS DOORS SHALL BE SIDE-HINGED SWINGING.
 - d. THE OPENING FORCE FOR INTERIOR SIDE-SWINGING DOORS WITHOUT CLOSERS SHALL NOT EXCEED A 5-POUND FORCE. FOR OTHER SIDE SWINGING, SLIDING AND FOLDING DOORS, THE DOOR LATCH SHALL RELEASE WHEN SUBJECTED TO A 15-POUND FORCE.
 - e. REVOLVING AND SLIDING DOORS MAY BE USED IN OTHER THAN THE FOLLOWING CIRCUMSTANCES AS EGRESS DOORS ONLY IF ALL OF THE REQUIREMENTS OF SECTION 1008.1.3.1 AND SECTION 1008.1.3.3, RESPECTIVELY, ARE MET.

PANIC AND FIRE EXIT HARDWARE, WHERE INSTALLED ON DOORS IN THIS BUILDING, SHALL SATISFY THE FOLLOWING: (1008.1.9)

- a. THE ACTUATING PORTION OF THE RELEASING DEVICE SHALL EXTEND AT LEAST ONE-HALF OF THE DOOR LEAF WIDTH.
- b. THE MAXIMUM LATCHING FORCE DOES NOT EXCEED 15 POUNDS.
- c. PIVOTED OR BALANCED DOORS SHALL BE OF THE PUSH-PAD TYPE WHERE PANIC HARDWARE IS REQUIRED, AND THE PAD SHALL NOT EXTEND ACROSS MORE THAN ONE-HALF OF THE DOOR WIDTH, MEASURED FROM THE LATCH SIDE.

WHERE KEY-OPERATED LOCKING DEVICES ARE USED, POST A SIGN ON OR ADJACENT TO THE REQUIRED MAIN EXIT DOOR WITH "IN. LETTERING STATING: "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED." (1008.1.8.3)

7. EGRESS DOORS OR GATES SHALL BE OPERABLE FROM THE EGRESS SIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE OR EFFORT. DOOR HANDLES, PULLS, LATCHES, LOCKS, AND OTHER OPERATING DEVICES SHALL BE INSTALLED 34 TO 48 IN. ABOVE THE FINISHED FLOOR. MANUALLY OPERATED FLUSH BOLTS OR SURFACE BOLTS ARE NOT PERMITTED. THE UNLATCHING OF ANY DOOR OR LEAF SHALL NOT REQUIRE MORE THAN ONE OPERATION. (1008.1.8)
9. THE FLOOR OR LANDING ON EACH SIDE OF DOORS SHALL NOT BE MORE THAN 1/2-IN. LOWER THAN THE THRESHOLD OF THE DOORWAY. RAISED THRESHOLDS AND FLOOR LEVEL CHANGES GREATER THAN 1/4-IN. AT DOORWAYS SHALL BE BEVELED WITH A SLOPE NOT GREATER THAN ONE UNIT VERTICAL IN TWO UNITS HORIZONTAL (50% SLOPE). (1008.1.6)

DOOR, WINDOW & FINISH SCHEDULES,
SECTION & INTERIOR ELEVATIONS

TORRANCE BUILDING DEPARTMENT
PERMIT CENTER PHASE II

3031 TORRANCE BOULEVARD
TORRANCE, CALIFORNIA 90503

WILLIAM LOYD JONES
ARCHITECT

723 oceanfront walk
venice, california
9 0 2 9 1

TEL 310 392 3995 FAX 310 392 2857

